



**Bearing No. 6202ZZE**

D	35 mm
d	15 mm
B	11 mm
C	11 mm
Noun	Bearing
Bore	0.591 Inch   15 Millimeter
Width	11 mm
UNSPSC	31171504
r min.	0.6 mm
Weight	0.045 Kg
da min.	20 mm
Da max.	30 mm
ra max.	0.6 mm
Category	Single Row Ball Bearing
ra (max)	0.6 mm
da (min)	20 mm
Da (max)	30 mm
Size (mm)	15x35x11
Snap Ring	No
Enclosure	2 Metal Shields
Bore Size	15 mm
Bore Type	Cylindrical Bore
Inventory	0.0
Factor fo	13.1
Width (mm)	11
Weight / LBS	0.099
Product Group	B00308
Configuration	Single Row
Cage Material	Steel

Inch - Metric	Metric
Keyword String	Ball
Other Features	Deep Groove
Bearing number	6202ZZE
Precision Class	ABEC 1   ISO P0
Rolling Element	Ball Bearing
Long Description	15MM Bore; 35MM Outside Diameter; 11MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Stee
Outer Race Width	0.433 Inch   11 Millimeter
Radial Clearance	0.003 to 0.018 mm
Inner Race Width	0 Inch   0 Millimeter
Manufacturer URL	<a href="http://www.nachi-america.com">http://www.nachi-america.com</a>
Outside Diameter	1.378 Inch   35 Millimeter
Manufacturer Name	NACHI
Weight / Kilogram	0
Internal Clearance	C0-Medium
Static Load Rating	3,700 N
Bore Diameter (mm)	15
Dynamic Load Rating	7,650 N
Outer Diameter (mm)	35
Minimum Buy Quantity	N/A
Fillet Radius/Chamfer	0.6 mm
Harmonized Tariff Code	8482.10.50.68
Limiting Speed - Grease	20,000 rpm
Internal Special	No

Features	
(Grease) Lubrication Speed	19000 r/min
Basic static load rating (C0)	3,7 kN
Basic dynamic load rating (C)	7,65 kN
Maximum Capacity / Filling Slot	No