



Bearing No. 74550/74850

e	0.49
d	139,7 mm
D	215,9 mm
T	47,625 mm
B	47,625 mm
C	34,925 mm
a	48,4 mm
Da	196 mm
B_	47.625
Db	208 mm
da	158 mm
Y0	0.68
db	151 mm
C0	495
D_	215.9
Z_	25
C_	34.925
Y1	1.2
DE_	193.043
SLR	33
D_a	196
DI_	161.315
DA1	17.193
DA2	15.471
CUP	1.99
DA_	16.336
D_b	208
RAr	328.415
SDM_	177.177
KBRG	3161

yobi	74550/74850
CONE	3.93
ALP21	36
ALP22	0
ALP23	0
BETA_	1
BET21	3
BET23	0
BET22	0
r min.	3,5 mm
LangID	1
Weight	5,92 Kg
ALPHA_	18
r1 min.	3,3 mm
ra max.	3,5 mm
Oil rpm	2000
outer r	3.3
hidYobi	74550/74850
GRS rpm	1500
inner r	3.5
hidTable	ecat_NSTPRI
inner ra	3.5
outer rb	3.3
ra1 max.	3,3 mm
Size (mm)	139.7x215.9x47.625
SHOG_yobi	74550/74850
Prod_Type3	TRBSR_ID_A
Width (mm)	47,625
Bearing number	74550/74850
Bore Diameter (mm)	139,7
Outer Diameter (mm)	215,9
Calculation factor (e)	0,49

(Oil) Lubrication Speed	2000 r/min
Calculation factor (Y0)	0,68
(Grease) Lubrication Speed	1500 r/min
Basic static load rating (C0)	495 kN
Basic dynamic load rating (C)	287 kN