



Bearing No. 6204

r	1
d	20 mm
D	47 mm
B	14 mm
C	14 mm
fo	13.1
D_	47
B_	14
ra	1
Z_	8
C0	6.6
DI_	25.562
SRE	4.21
D_a	42
DE_	41.438
SRI	4.01
DA_	7.938
SREN	0
Noun	Bearing
SRIN	0
bomp	0
SRIX	0.02
yobi	6204
mass	0.107
SDM_	33.5
KBRG	6101
SREX	0.04
SBRG	2
Bore	0.787 Inch 20 Millimeter

LangID	1
Weight	0,107 Kg
r min.	1 mm
ALPHA_	0
C_conv	12800
da min	25
UNSPSC	31171504
da max	26,5 mm
Oil rpm	18000
GRS rpm	15000
ra max.	1 mm
hidYobi	6204
Da max.	42 mm
da min.	25 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Inventory	6.0
Snap Ring	No
Enclosure	Open
Size (mm)	20x47x14
Prod_Type3	DGBB_SR_OT
bore type:	Round
Width (mm)	14
Weight / LBS	0.23
Inch - Metric	Metric
closure type:	Open
Product Group	B00308
Cage Material	Steel
Keyword String	Ball
overall width:	14 mm
Bearing number	6204
bore diameter:	20 mm

Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outer Race Width	0.551 Inch 14 Millimeter
Long Description	20MM Bore; 47MM Outside Diameter; 14MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer URL	http://www.nskamericas.com
Outside Diameter	1.85 Inch 47 Millimeter
Weight / Kilogram	0.1
Manufacturer Name	NSK
outside diameter:	47 mm
Internal Clearance	C0-Medium
Bore Diameter (mm)	20
Outer Diameter (mm)	47
internal clearance:	Normal Clearance
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	18 000 r/min
manufacturer upc number:	029176014215
Manufacturer Item Number	6204
Internal Special Features	No
(Grease) Lubrication Speed	15 000 r/min
Basic dynamic load rating (C)	12,8 kN
Basic static load rating (C0)	6,6 kN

Maximum Capacity / Filling Slot	No
------------------------------------	----