



Bearing No. K65X73X30H

Fw	65 mm
Ew	74 mm
Bc	30 mm
Cr	60.1
Cu	20.3
P/S	S
C0r	129
Noun	Bearing
Bore	2.559 Inch 65 Millimeter
Width	1.181 Inch 30 Millimeter
UNSPSC	31171512
Weight	0.116 Kg
Retainer	Yes
Oil lub.	6500
Category	Needle Non Thrust Roller Bearing
Inventory	0.0
Separable	No
Component	Roller Assembly Only
Enclosure	Not Applicable
Closed End	Not Applicable
Grease lub.	4200
Bearing No.	K65X73X30H
Shaft(max.)	65.000
Shaft(min.)	64.987
Weight / LBS	0.256
Housing(max.)	73.029
Housing(min.)	73.010
Inch - Metric	Metric

Product Group	B04144
Self Aligning	No
Other Features	Radial Roller Hardened Steel Cage
Bearing number	K65X73X30H
Keyword String	Needle
Thrust Bearing	No
Rolling Element	Needle Roller Bearing
Outside Diameter	2.874 Inch 73 Millimeter
Long Description	65MM Bore; 73MM Outside Diameter; 30MM Width; Needle Roller Bearing; Roller Assembly Only; No Self Aligning; Retainer; Single Row of Rollers; No Separable
Manufacturer URL	http://www.koyousa.com
(Refer.)Mass(kg)	0.116
Manufacturer Name	KOYO
Weight / Kilogram	0.12
Bore Diameter (mm)	65
Outer Diameter (mm)	74
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.40.00.00
(Oil) Lubrication Speed	6500 r/min
Manufacturer Item Number	K65X73X30H
Number of Rows of Rollers	Single Row
(Grease) Lubrication Speed	4200 r/min
Basic static load rating (C0)	129 kN
Basic dynamic load	60.1 kN

rating (C)	
------------	--