



Bearing No. 36990/36920

e	0.44
d	177,8 mm
D	227,012 mm
T	30,162 mm
B	30,162 mm
C	23,02 mm
a	42,9 mm
Da	214 mm
B_	30.162
Db	221 mm
da	189 mm
Y0	0.75
db	186 mm
C0	415
D_	227.012
Z_	50
C_	23.02
Y1	1.4
DE_	212.351
SLR	21
D_a	214
DI_	193.345
DA1	10.148
DA2	9.6
CUP	0.907
DA_	9.87
D_b	221
RAr	387.655
SDM_	202.977
KBRG	3161

yobi	36990/36920
CONE	2.1
ALP21	32
ALP22	40
ALP23	0
BETA_	0
BET21	1
BET23	0
BET22	30
r min.	1,5 mm
LangID	1
Weight	3,007 Kg
ALPHA_	16.367
r1 min.	1,5 mm
ra max.	1,5 mm
Oil rpm	1800
outer r	1.5
hidYobi	36990/36920
GRS rpm	1300
inner r	1.5
hidTable	ecat_NSTPRI
inner ra	1.5
outer rb	1.5
ra1 max.	1,5 mm
Size (mm)	177.8x227.012x30.162
SHOG_yobi	36990/36920
Prod_Type3	TRBSR_ID_A
Width (mm)	30,162
Bearing number	36990/36920
Bore Diameter (mm)	177,8
Outer Diameter (mm)	227,012
Calculation factor (e)	0,44

(Oil) Lubrication Speed	1800 r/min
Calculation factor (Y0)	0,75
(Grease) Lubrication Speed	1300 r/min
Basic static load rating (C0)	415 kN
Basic dynamic load rating (C)	181 kN