



Bearing No. 6204DDU

r	1
d	20 mm
D	47 mm
B	14 mm
C	14 mm
D_	47
C0	6.6
Z_	8
ra	1
fo	13.1
B_	14
DI_	25.562
SRI	4.01
SRE	4.21
DE_	41.438
DA_	7.938
D_a	42
KBRG	6161
SBRG	2
SRIN	0
bomp	0
SREX	0.04
yobi	6204DDU
SRIX	0.02
Bore	0.787 Inch 20 Millimeter
SDM_	33.5
SREN	0
mass	0.107
Noun	Bearing

LangID	1
UNSPSC	31171504
da min	25
r min.	1 mm
Weight	0,107 Kg
ALPHA_	0
C_conv	12800
da max	26,5 mm
GRS rpm	11000
Da max.	42 mm
ra max.	1 mm
da min.	25 mm
hidYobi	6204DDU
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Size (mm)	20x47x14
Enclosure	2 Seals
Snap Ring	No
Inventory	0.0
Width (mm)	14
Prod_Type3	DGBB_SR_DD
Weight / LBS	0.2359
Inch - Metric	Metric
Product Group	B00308
Cage Material	Steel
Bearing number	6204DDU
Keyword String	Ball
Other Features	Deep Groove Rubber Seal
Enclosure Type	Contact Seal
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outside Diameter	1.85 Inch 47 Millimeter

Inner Race Width	0 Inch 0 Millimeter
Long Description	20MM Bore; 47MM Outside Diameter; 14MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Manufacturer URL	http://www.nskamericas.com
Outer Race Width	0.551 Inch 14 Millimeter
Manufacturer Name	NSK
Weight / Kilogram	0.103
Internal Clearance	C0-Medium
Bore Diameter (mm)	20
Outer Diameter (mm)	47
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6204DDU
Internal Special Features	No
(Grease) Lubrication Speed	11 000 r/min
Basic static load rating (C0)	6,6 kN
Basic dynamic load rating (C)	12,8 kN
Maximum Capacity / Filling Slot	No