




Bearing No. 7200BDF

D	30 mm
a	3.9 mm
C	9 mm
B	9 mm
d	10 mm
r1	0.3 mm
2B	18 mm
Width	9 mm
r min.	0.6 mm
Weight	0.034 Kg
ra max.	0.3 mm
r1 min.	0.3 mm
da min.	12 mm
Da max.	27.4 mm
ra (max)	0.6 mm
da1 (min)	15 mm
Bore Size	10 mm
Enclosure	Open
Bore Type	Cylindrical Bore
ra1 (max)	0.3 mm
Size (mm)	10x30x9
da2 (min)	12 mm
Da2 (max)	27.4 mm
Da1 (max)	25 mm
Width (mm)	9
Configuration	Duplex
Bearing number	7200BDF
Angle (?)	40 °
Outside Diameter	30 mm
Static Load Rating	5,150 N

Bore Diameter (mm)	10
Dynamic Load Rating	8,350 N
Outer Diameter (mm)	30
Limiting Speed - Oil	22,000 rpm
Fillet Radius/Chamfer	0.6 mm
Limiting Speed - Grease	16,000 rpm
(Grease) Lubrication Speed	16000 r/min
Basic dynamic load rating (C)	8,35 kN
Basic static load rating (C0)	5,15 kN