



Bearing No. K75X83X30FH

Fw	75 mm
Ew	86 mm
Bc	30 mm
Cr	60.9
Cu	21.7
P/S	S
C0r	138
Noun	Bearing
Bore	2.953 Inch 75 Millimeter
Width	1.181 Inch 30 Millimeter
UNSPSC	31171512
Weight	0.141 Kg
Retainer	Yes
Oil lub.	5600
Category	Needle Non Thrust Roller Bearing
Inventory	0.0
Separable	No
Component	Roller Assembly Only
Enclosure	Not Applicable
Closed End	Not Applicable
Grease lub.	3600
Bearing No.	K75X83X30FH
Shaft(max.)	75.000
Shaft(min.)	74.987
Weight / LBS	0.311
Housing(max.)	83.034
Housing(min.)	83.012
Inch - Metric	Metric

Product Group	B04144
Self Aligning	No
Other Features	Radial Roller Machined Steel Cage
Bearing number	K75X83X30FH
Keyword String	Needle
Thrust Bearing	No
Rolling Element	Needle Roller Bearing
Outside Diameter	3.268 Inch 83 Millimeter
Long Description	75MM Bore; 83MM Outside Diameter; 30MM Width; Needle Roller Bearing; Roller Assembly Only; No Self Aligning; Retainer; Single Row of Rollers; No Separable
Manufacturer URL	http://www.koyousa.com
(Refer.)Mass(kg)	0.141
Manufacturer Name	KOYO
Weight / Kilogram	0.14
Bore Diameter (mm)	75
Outer Diameter (mm)	86
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.40.00.00
(Oil) Lubrication Speed	5600 r/min
Manufacturer Item Number	K75X83X30FH
Number of Rows of Rollers	Single Row
(Grease) Lubrication Speed	3600 r/min
Basic static load rating (C0)	138 kN
Basic dynamic load	60.9 kN



rating (C)	
------------	--