



Bearing No. 7407 BM

a	41 mm
d	35 mm
D	100 mm
B	25 mm
Noun	Bearing
Bore	1.378 Inch 35 Millimeter
Width	0.984 Inch 25 Millimeter
UNSPSC	31171531
series:	74
Category	Angular Contact Ball Bearing
Enclosure	Open
Snap Ring	No
Size (mm)	100x35x25
Inventory	0.0
Width (mm)	25
Weight / LBS	2.321
maximum rpm:	9000 RPM
Flush Ground	No
Mass bearing	1.1 kg
Contact Angle	40 Degree
Cage Material	Brass
closure type:	Open
Product Group	B00308
Inch - Metric	Metric
d ₁	61.95 mm
d ₂	50.75 mm
D ₁	76.1 mm

Bearing number	7407 BM
Keyword String	Angular Contact
fillet radius:	1.5 mm
contact angle:	40 °
overall width:	25 mm
cage material:	Brass
bore diameter:	35 mm
Limiting speed	9000 r/min
finish/coating:	Uncoated
Reference speed	8500 r/min
Rolling Element	Ball Bearing
Precision Class	ABEC 3 ISO P6
Outside Diameter	3.937 Inch 100 Millimeter
Manufacturer URL	http://www.skf.com
Long Description	35MM Bore; 100MM Outside Diameter; 25MM Width; Open; No Flush Ground; Ball Bearing; Single Row of Balls; ABEC 3 ISO P6; No Filling Slot; No Snap Ring
outer ring width:	25 mm
outside diameter:	100 mm
precision rating:	ABEC 3 (ISO Class 6)
Manufacturer Name	SKF
Weight / Kilogram	1.05
Number of Bearings	1 (Single)
Internal Clearance	C0-Medium
d _a min.	55 mm
Bore Diameter (mm)	100
D _a max.	110 mm
D _b max.	89.4 mm
r _a max.	2 mm

r_b max.	2 mm
Outer Diameter (mm)	35
internal clearance:	C0
$r_{1,2}$ min.	1.5 mm
Calculation factor A	0.0276
Calculation factor e	1.14
Calculation factor X	0.57
$r_{3,4}$ min.	1.5 mm
Minimum Buy Quantity	N/A
D_a - max.	110 mm
r_b - max.	2 mm
r_a - max.	2 mm
D_b - max.	89.4 mm
d_a - min.	55 mm
d_2 ?	50.75 mm
D_1 ?	76.1 mm
d_1 ?	61.95 mm
row type & fill slot:	Single-Row Non-Fill Slot
Calculation factor - X	0.35
Calculation factor - e	1.14
Harmonized Tariff Code	8482.10.50.28
$r_{1,2}$ - min.	1.5 mm
$r_{3,4}$ - min.	1.5 mm
Number of Rows of Balls	Single Row
Manufacturer Item Number	7407 BM
Basic dynamic load rating C	60.5 kN
radial static load capacity:	38 kN
Basic dynamic load rating - C	60.5 kN
radial dynamic load capacity:	60.5 kN

Maximum Capacity / Filling Slot	No
Calculation factor Y_1	0.55
Calculation factor Y_2	0.93
Calculation factor k_r	0.1
Fatigue load limit P_u	1.6 kN
Calculation factor Y_0	0.52
Fatigue load limit - P_u	1.6 kN
Calculation factor - Y_2	0.57
Calculation factor - Y_1	
Calculation factor - k_a	1.6
Calculation factor - Y_0	0.26
Calculation factor - k_r	0.1
Basic static load rating C_0	38 kN
Basic static load rating - C_0	38 kN