




Bearing No. 6205-2Z/VA228

D	52 mm
d	25 mm
B	15 mm
Bore	0.984 Inch 25 Millimeter
Noun	Bearing
UNSPSC	31171504
series:	62
Category	Single Row Ball Bearing
Inventory	0.0
Snap Ring	No
Size (mm)	52x25x15
Enclosure	2 Metal Shields
bore type:	Round
Width (mm)	15
maximum rpm:	230 RPM
Weight / LBS	0.302
Mass bearing	0.13 kg
Product Group	B00308
Inch - Metric	Metric
Cage Material	Graphite
closure type:	Double Shielded
D ₂	46.21 mm
d ₁	34.35 mm
Keyword String	Ball
bore diameter:	25 mm
cage material:	Graphite
fillet radius:	1 mm
Other Features	Deep Groove Extreme Temperature Variant

overall width:	15 mm
Bearing number	6205-2Z/VA228
Limiting speed	230 r/min
Rolling Element	Ball Bearing
finish/coating:	Uncoated
Precision Class	ABEC 1 ISO P0
Manufacturer URL	http://www.skf.com
Outside Diameter	2.047 Inch 52 Millimeter
Outer Race Width	0.591 Inch 15 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Long Description	25MM Bore; 52MM Outside Diameter; 15MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; Coronet Cage Internal Special Features; C0-Medium Internal Clear
Manufacturer Name	SKF
outer ring width:	15 mm
Weight / Kilogram	0.137
precision rating:	Not Rated
outside diameter:	52 mm
D _a max.	46.4 mm
Bore Diameter (mm)	52
d _a min.	30.6 mm
r _a max.	1 mm
Internal Clearance	C0-Medium
d _a max.	34.3 mm
internal clearance:	C0
Outer Diameter (mm)	25
	30.6 mm

d ^a - min.	
-----------------------	--

D_a - max.	46.4 mm
d_a - max.	34.3 mm
r_a - max.	1 mm
$r_{1,2}$ min.	1 mm
Minimum Buy Quantity	N/A
resistance features:	Corrosion Resistant, Extreme Temperature
D_2 ?	46.21 mm
row type & fill slot:	Single Row Non-Fill Slot
static load capacity:	7.8 kN
d_1 ?	34.35 mm
Harmonized Tariff Code	8482.10.50.68
$r_{1,2}$ - min.	1 mm
Manufacturer Item Number	6205-2Z/VA228
Limiting temperature - T	350 °C
Internal Special Features	Coronet Cage
Basic dynamic load rating C	14.8 kN
Limiting temperature T max.	350 °C
operating temperature range:	-240 to +660 °F
Basic dynamic load rating - C	14.8 kN
Maximum Capacity / Filling Slot	No
Basic static load rating C_0	7.8 kN
Basic static load rating - C_0	7.8 kN