



Bearing No. 7201BDT

D	32 mm
a	4.2 mm
C	10 mm
B	10 mm
d	12 mm
r1	0.3 mm
2B	20 mm
Width	10 mm
r min.	0.6 mm
Weight	0.040 Kg
ra max.	0.3 mm
r1 min.	0.3 mm
da min.	14 mm
Da max.	29.4 mm
ra (max)	0.6 mm
da1 (min)	17 mm
Bore Size	12 mm
Enclosure	Open
Bore Type	Cylindrical Bore
ra1 (max)	0.3 mm
Size (mm)	12x32x10
da2 (min)	14 mm
Da2 (max)	29.4 mm
Da1 (max)	27 mm
Width (mm)	10
Configuration	Duplex
Bearing number	7201BDT
Angle (?)	40 °
Outside Diameter	32 mm
Static Load Rating	7,550 N

Bore Diameter (mm)	12
Dynamic Load Rating	11,700 N
Outer Diameter (mm)	32
Limiting Speed - Oil	20,000 rpm
Fillet Radius/Chamfer	0.6 mm
Limiting Speed - Grease	15,000 rpm
(Grease) Lubrication Speed	15000 r/min
Basic dynamic load rating (C)	11,7 kN
Basic static load rating (C0)	7,55 kN