



Bearing No. 67885/67820

e	0.48
d	190,5 mm
D	266,7 mm
T	47,625 mm
B	46,833 mm
C	38,1 mm
a	57,9 mm
Da	246 mm
B_	46.833
Db	259 mm
da	209 mm
Y0	0.69
db	203 mm
C0	720
D_	266.7
Z_	38
C_	38.1
Y1	1.3
DE_	244.394
SLR	33
D_a	246
DI_	215.023
DA1	15.847
DA2	14.602
CUP	2.64
DA_	15.226
D_b	259
RAr	419.101
SDM_	229.812
KBRG	3161

yobi	67885/67820
CONE	5.4
ALP21	35
ALP22	20
ALP23	0
BETA_	1
BET21	2
BET23	0
BET22	10
r min.	3,5 mm
LangID	1
Weight	8,04 Kg
ALPHA_	17.667
r1 min.	3,3 mm
ra max.	3,5 mm
Oil rpm	1500
outer r	3.3
hidYobi	67885/67820
GRS rpm	1100
inner r	3.5
hidTable	ecat_NSTPRI
inner ra	3.5
outer rb	3.3
ra1 max.	3,3 mm
Size (mm)	190.5x266.7x47.625
SHOG_yobi	67885/67820
Prod_Type3	TRBSR_ID_A
Width (mm)	47,625
Bearing number	67885/67820
Bore Diameter (mm)	190,5
Outer Diameter (mm)	266,7
Calculation factor (e)	0,48

(Oil) Lubrication Speed	1500 r/min
Calculation factor (Y0)	0,69
(Grease) Lubrication Speed	1100 r/min
Basic static load rating (C0)	720 kN
Basic dynamic load rating (C)	345 kN