



Bearing No. 66585/66520

e	0.67
d	60 mm
D	122,238 mm
T	33,338 mm
B	31,75 mm
C	23,812 mm
a	34,3 mm
Da	105 mm
B_	31.75
Db	116 mm
da	79 mm
Y0	0.5
db	73 mm
C0	156
D_	122.238
Z_	15
C_	23.812
Y1	0.9
DE_	105.114
SLR	21
D_a	105
DI_	74.922
DA1	17.01
DA2	14.477
CUP	0.558
DA_	15.761
D_b	116
RAr	139.346
SDM_	89.894
KBRG	3161

yobi	66585/66520
CONE	1.07
ALP21	47
ALP22	50
ALP23	0
BETA_	3
BET21	7
BET23	0
BET22	0
r min.	3,5 mm
LangID	1
Weight	1,628 Kg
ALPHA_	23.917
r1 min.	3,3 mm
ra max.	3,5 mm
Oil rpm	4000
outer r	3.3
hidYobi	66585/66520
GRS rpm	3000
inner r	3.5
hidTable	ecat_NSTPRI
inner ra	3.5
outer rb	3.3
ra1 max.	3,3 mm
Size (mm)	60x122.238x33.338
SHOG_yobi	66585R/66520R
Prod_Type3	TRBSR_ID_A
Width (mm)	33,338
Bearing number	66585/66520
Bore Diameter (mm)	60
Outer Diameter (mm)	122,238
Calculation factor (e)	0,67

(Oil) Lubrication Speed	4000 r/min
Calculation factor (Y0)	0,5
(Grease) Lubrication Speed	3000 r/min
Basic static load rating (C0)	156 kN
Basic dynamic load rating (C)	135 kN