



Bearing No. 7203BDB

D	40 mm
a	6.0 mm
C	12 mm
B	12 mm
d	17 mm
r1	0.3 mm
2B	24 mm
Width	12 mm
r min.	0.6 mm
Weight	0.070 Kg
ra max.	0.3 mm
r1 min.	0.3 mm
da min.	19 mm
Da max.	37.4 mm
ra (max)	0.6 mm
da1 (min)	22 mm
Bore Size	17 mm
Enclosure	Open
Bore Type	Cylindrical Bore
ra1 (max)	0.3 mm
Size (mm)	17x40x12
da2 (min)	19 mm
Da2 (max)	37.4 mm
Da1 (max)	35 mm
Width (mm)	12
Configuration	Duplex
Bearing number	7203BDB
Angle (?)	40 °
Outside Diameter	40 mm
Static Load Rating	12,600 N

Bore Diameter (mm)	17
Dynamic Load Rating	18,400 N
Outer Diameter (mm)	40
Limiting Speed - Oil	15,000 rpm
Fillet Radius/Chamfer	0.6 mm
Limiting Speed - Grease	11,000 rpm
(Grease) Lubrication Speed	11000 r/min
Basic dynamic load rating (C)	18,4 kN
Basic static load rating (C0)	12,6 kN