



Bearing No. 387A/382A

|           |                 |
|-----------|-----------------|
| C         | 15,875 mm       |
| a         | 17,4 mm         |
| e         | 0.35            |
| d         | 57,15 mm        |
| D         | 96,838 mm       |
| T         | 21 mm           |
| B         | 21,946 mm       |
| db        | 62.0            |
| da        | 69.0            |
| Cr        | 101             |
| Da        | 89 mm           |
| Db        | 92 mm           |
| Cu        | 15.3            |
| Y1        | 1.69            |
| Y0        | 0.93            |
| C0r       | 101             |
| a(mm)     | 17.4            |
| Weight    | 0,603 Kg        |
| r(min)    | 3.6             |
| db min    | 62 mm           |
| r min.    | 3,6 mm          |
| ra max.   | 3,6 mm          |
| r1(min)   | 0.8             |
| rb(max)   | 0.8             |
| ra(max)   | 3.6             |
| da min.   | 69 mm           |
| r2 min.   | 0,8 mm          |
| rb max.   | 0,8 mm          |
| Oil lub.  | 5200            |
| Size (mm) | 57.15x96.838x21 |
|           |                 |

|                               |            |
|-------------------------------|------------|
| Width (mm)                    | 21         |
| Bearing No.                   | 387A/382A  |
| Grease lub.                   | 3900       |
| Bearing number                | 387A/382A  |
| (Refer.)Mass(kg)              | 0.603      |
| Bore Diameter (mm)            | 57,15      |
| Outer Diameter (mm)           | 96,838     |
| Calculation factor (e)        | 0,35       |
| Calculation factor (Y0)       | 0,93       |
| (Oil) Lubrication Speed       | 5200 r/min |
| (Grease) Lubrication Speed    | 3900 r/min |
| Basic dynamic load rating (C) | 80,4 kN    |
| Basic static load rating (C0) | 101 kN     |