




Bearing No. 6206NR

f	1,65 mm
d	30 mm
D	62 mm
B	16 mm
C	16 mm
a	3,28 mm
b	2,05 mm
Cr	24.3
f0	13.9
Cu	0.800
D2	67,7 mm
D1	59,61 mm
C0r	11.3
Bore	1.181 Inch 30 Millimeter
Noun	Bearing
r min.	1 mm
r(min)	1
UNSPSC	31171504
Weight	0,199 Kg
r1(min)	0.5
da(min)	35
D2(min)	67.7
Da(max)	57
rb(max)	0.5
ra(max)	1
Dx(min)	68.5
r0 max.	0,6 mm
r1 min.	0,5 mm
da min.	35 mm

Cy(max)	4.67
Da max.	57 mm
Category	Single Row Ball Bearing
Oil lub.	13000
Snap Ring	Yes
Size (mm)	30x62x16
Inventory	0.0
Enclosure	Open
Width (mm)	16
Grease lub.	11000
f{0.05)	1.65
Bearing No.	6206NR
Weight / LBS	0.43872
Cage Material	Steel
Inch - Metric	Metric
Product Group	B00308
Bearing number	6206NR
Other Features	Deep Groove With Snap Ring
Keyword String	Ball
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Manufacturer URL	http://www.koyousa.com
Outside Diameter	2.441 Inch 62 Millimeter
(Refer.)Mass(kg)	0.199
Long Description	30MM Bore; 62MM Outside Diameter; 16MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; Yes Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage

Outer Race Width	0.63 Inch 16 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Weight / Kilogram	0.221
Manufacturer Name	KOYO
Internal Clearance	C0-Medium
Bore Diameter (mm)	30
Outer Diameter (mm)	62
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	13000 r/min
Internal Special Features	No
(Grease) Lubrication Speed	11000 r/min
Basic static load rating (C0)	11,3 kN
Basic dynamic load rating (C)	19,5 kN
Maximum Capacity / Filling Slot	No