



Bearing No. 395/394A

e	0.4
d	63,5 mm
D	110 mm
T	22 mm
B	21,996 mm
C	18,824 mm
a	20,9 mm
Da	101 mm
B_	21.996
Db	104 mm
da	77 mm
Y0	0.82
db	70 mm
C0	113
D_	110
Z_	22
C_	18.824
Y1	1.5
DE_	99.06
SLR	14.2
D_a	101
DI_	77.704
DA1	10.871
DA2	10.09
CUP	0.263
DA_	10.483
D_b	104
RAr	196.722
SDM_	87.996
KBRG	3161

yobi	395/394A
CONE	0.58
ALP21	30
ALP22	0
ALP23	0
BETA_	1
BET21	3
BET23	0
BET22	10
r min.	3,5 mm
LangID	1
Weight	0,843 Kg
ALPHA_	15
r1 min.	1,3 mm
ra max.	3,5 mm
Oil rpm	4300
outer r	1.3
hidYobi	395/394A
GRS rpm	3200
inner r	3.5
hidTable	ecat_NSTPRI
inner ra	3.5
outer rb	1.3
ra1 max.	1,3 mm
Size (mm)	63.5x110x22
SHOG_yobi	395R/394AR
Prod_Type3	TRBSR_ID_A
Width (mm)	22
Bearing number	395/394A
Bore Diameter (mm)	63,5
Outer Diameter (mm)	110
Calculation factor (e)	0,4

(Oil) Lubrication Speed	4300 r/min
Calculation factor (Y0)	0,82
(Grease) Lubrication Speed	3200 r/min
Basic static load rating (C0)	113 kN
Basic dynamic load rating (C)	85,5 kN