



Bearing No. 641/633

|                                 |                       |
|---------------------------------|-----------------------|
| R                               | 3,6 mm                |
| d                               | 66,675 mm             |
| D                               | 130,175 mm            |
| T                               | 41,275 mm             |
| B                               | 41,275 mm             |
| C                               | 31,75 mm              |
| r                               | 3,3 mm                |
| Da                              | 124 mm                |
| Ab                              | 1,9 mm                |
| Aa                              | 4,2 mm                |
| Db                              | 116 mm                |
| da                              | 77 mm                 |
| db                              | 83 mm                 |
| a -                             | 11,2 mm               |
| Weight                          | 2,39 Kg               |
| Size (mm)                       | 66.675x130.175x41.275 |
| Width (mm)                      | 41,275                |
| Factor (K)                      | 1,61                  |
| Factor (G1)                     | 106,4                 |
| Factor (Cg)                     | 0,0205                |
| Factor (G2)                     | 21                    |
| Bearing number                  | 641/633               |
| Bore Diameter (mm)              | 66,675                |
| Outer Diameter (mm)             | 130,175               |
| Calculation factor (e)          | 0,36                  |
| Basic static load rating (C0)   | 298 kN                |
| Basic dynamic load rating (C1)  | 216 kN                |
| Basic dynamic load rating (C90) | 55,9                  |

|                                  |      |
|----------------------------------|------|
| Basic dynamic load rating (Ca90) | 34,7 |
|----------------------------------|------|