



Bearing No. 6208DDU

r	1.1
d	40 mm
D	80 mm
B	18 mm
C	18 mm
D_	80
C0	17.9
Z_	9
ra	1
fo	14
B_	18
DI_	48.094
SRI	6.16
SRE	6.16
DE_	71.906
DA_	11.906
D_a	73.5
KBRG	6161
SBRG	2
SRIN	-0.025
bomp	0
SREX	0.025
yobi	6208DDU
SRIX	0.025
Bore	1.575 Inch 40 Millimeter
SDM_	60
SREN	-0.025
mass	0.366
Noun	Bearing

LangID	1
UNSPSC	31171504
da min	46.5
ALPHA_	0
r min.	1,1 mm
Weight	0,366 Kg
C_conv	29100
da max	50,5 mm
Da max.	73,5 mm
ra max.	1 mm
GRS rpm	5600
da min.	46,5 mm
hidYobi	6208DDU
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Size (mm)	40x80x18
Enclosure	2 Seals
Snap Ring	No
Inventory	0.0
Width (mm)	18
Prod_Type3	DGBB_SR_DD
Weight / LBS	0.807
Inch - Metric	Metric
Product Group	B00308
Cage Material	Steel
Bearing number	6208DDU
Keyword String	Ball
Other Features	Deep Groove Rubber Seal
Enclosure Type	Contact Seal
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outer Race Width	0.709 Inch 18

	Millimeter
Outside Diameter	3.15 Inch 80 Millimeter
Long Description	40MM Bore; 80MM Outside Diameter; 18MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Manufacturer URL	http://www.nskamericas.com
Inner Race Width	0 Inch 0 Millimeter
Manufacturer Name	NSK
Weight / Kilogram	0.365
Internal Clearance	C0-Medium
Bore Diameter (mm)	40
Outer Diameter (mm)	80
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6208DDU
Internal Special Features	No
(Grease) Lubrication Speed	5 600 r/min
Basic static load rating (C0)	17,9 kN
Basic dynamic load rating (C)	29,1 kN
Maximum Capacity / Filling Slot	No