




Bearing No. NUP 313 ECP

F	82.5 mm
D	140 mm
B	33 mm
d	65 mm
Noun	Bearing
Bore	2.559 Inch 65 Millimeter
Width	1.299 Inch 33 Millimeter
UNSPSC	31171547
series:	NUP3
Profile	Complete with Outer and Inner Ring
Retainer	Yes
flanges:	(4) Flanges, Two-Piece Inner Ring
Category	Cylindrical Roller Bearing
Separable	No
Size (mm)	140x65x33
Inventory	1.0
Snap Ring	No
Width (mm)	33
bore type:	Straight
Bore Profile	Straight
Mass bearing	2.35 kg
Weight / LBS	5.3
maximum rpm:	6000 RPM
application:	Piston Type Machines, Rolling Mills, Spindles/Machine Tools
closure type:	Open

Product Group	B04144
D ₁	117.4 mm
Cage Material	Polymer
Inch - Metric	Metric
d ₁	90.5 mm
overall width:	33 mm
cage material:	Polyamide
Other Features	High Capacity 1 Rib Inner Ring with Side Plate 2 Rib Outer Ring Cage on Outer Ring ID
Relubricatable	Yes
fillet radius:	2 mm
bore diameter:	65 mm
Bearing number	NUP 313 ECP
Limiting speed	6000 r/min
finish/coating:	Uncoated
Reference speed	5300 r/min
number of rows:	1
Rolling Element	Cylindrical Roller Bearing
Precision Class	RBEC 1 ISO P0
ring separation:	Separable Ring
Long Description	65MM Bore; Straight Bore Profile; 140MM Outside Diameter; 33MM Width; Polymer Cage Matetrial; RBEC 1 ISO P0; Single Row; Not Separable; No Snap Ring; Relubricatable; C0-Medium Internal Clearance; Re
Limiting value e	0.2
Outside Diameter	5.512 Inch 140 Millimeter

Manufacturer URL	http://www.skf.com
Manufacturer Name	SKF
precision rating:	RBEC 1 (ISO Class Normal)
outside diameter:	140 mm
outer ring width:	33 mm
bearing material:	Steel
Weight / Kilogram	2.406
d _b min.	93 mm
D _a max.	127.8 mm
d _a min.	77 mm
Bore Diameter (mm)	140
r _a max.	2 mm
Internal Clearance	C0-Medium
Axial load factor Y	0.6
internal clearance:	C0
Outer Diameter (mm)	65
d _a - min.	77 mm
D _a - max.	127.8 mm
Minimum Buy Quantity	N/A
r _a - max.	2 mm
r _{3,4} min.	2.1 mm
r _{1,2} min.	2.1 mm
d _b - min.	93 mm
d ₁ ?	90.5 mm
D ₁ ?	117.4 mm
static load capacity:	196 kN
dynamic load capacity:	212 kN
r _{1,2} - min.	2.1 mm
r _{3,4} - min.	2.1 mm
Harmonized Tariff Code	8482.50.00.00
Manufacturer Item Number	NUP 313 ECP

Number of Rows of Rollers	Single Row
Basic dynamic load rating C	212 kN
operating temperature range:	Maximum of +300 °F
Basic dynamic load rating - C	212 kN
Fatigue load limit P_u	25.5 kN
Calculation factor k_r	0.15
Fatigue load limit - P_u	25.5 kN
Calculation factor - k_r	0.15
Basic static load rating C_0	196 kN
Basic static load rating - C_0	196 kN