




Bearing No. 7207BG

D	72,000 mm
d	35,000 mm
B	17,000 mm
C	17,000 mm
a	31 mm
Mass	0.29 kg
Noun	Bearing
Bore	1.378 Inch 35 Millimeter
Width	0.669 Inch 17 Millimeter
Da max	65 mm
Db max	67.5 mm
UNSPSC	31171531
ra max	1 mm
rs min	1.1 mm
da min	42 mm
db min	39.5 mm
r1s min	0.6 mm
r1a max	0.6 mm
series:	72B
weight:	0.289 kg
Category	Angular Contact Ball Bearing
Inventory	0.0
Enclosure	Open
Snap Ring	No
Size (mm)	35x72x17
Nlim (oil)	12,000 rpm
bore type:	Round
Width (mm)	17,000

Flush Ground	Yes
Weight / LBS	0.639
maximum rpm:	12000 rpm
Cage Material	Steel
Contact Angle	40 Degree
Product Group	B00308
Inch - Metric	Metric
Nlim (grease)	9,300 rpm
closure type:	Open
bore diameter:	35 mm
cage material:	Steel
Keyword String	Angular Contact
contact angle:	40 °
fillet radius:	1.1 mm
overall width:	17 mm
Bearing number	7207BG
Dynamic load, C	27.1 kN
finish/coating:	Uncoated
Precision Class	ABEC 1 ISO P0
Static load, C0	18.4 kN
Rolling Element	Ball Bearing
Long Description	35MM Bore; 72MM Outside Diameter; 17MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 1 ISO P0; No Filling Slot; No Snap Ring
Manufacturer URL	http://www.ntnamerica.com
Outside Diameter	2.835 Inch 72 Millimeter
Contact angle ?	40 °
Manufacturer Name	NTN

bearing material:	High Carbon Chrome Steel
precision rating:	ISO Class 0
outer ring width:	17 mm
Weight / Kilogram	0.289
outside diameter:	72 mm
Number of Bearings	1 (Single)
Bore Diameter (mm)	35,000
Internal Clearance	C0-Medium
Outer Diameter (mm)	72,000
snap ring included:	Without Snap Ring
internal clearance:	C0
Minimum Buy Quantity	N/A
Mounting Arrangement	Universal
row type & fill slot:	Single-Row Non-Fill Slot
Fatigue limit load, Cu	0.84 kN
Harmonized Tariff Code	8482.10.50.28
Radial clearance class	CN
Number of Rows of Balls	Single Row
Manufacturer Item Number	7207BG
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
radial static load capacity:	18400 N
radial dynamic load capacity:	27100 N
Min operating temperature, Tmin	-40 °C
Maximum Capacity / Filling Slot	No
Max operating temperature, Tmax	120 °C

