




Bearing No. 7321 BECBM

a	94 mm
d	105 mm
D	225 mm
B	49 mm
Noun	Bearing
Bore	4.134 Inch 105 Millimeter
Width	1.929 Inch 49 Millimeter
UNSPSC	31171531
series:	73
Category	Angular Contact Ball Bearing
Enclosure	Open
Snap Ring	No
Size (mm)	225x105x49
Inventory	0.0
Width (mm)	49
Weight / LBS	20.097
maximum rpm:	3800 RPM
Flush Ground	Yes
Mass bearing	8.55 kg
Contact Angle	40 Degree
Cage Material	Brass
closure type:	Open
Product Group	B00308
Inch - Metric	Metric
d ₁	151.65 mm
D ₁	181.35 mm
d ₂	127.87 mm

Bearing number	7321 BECBM
bore diameter:	105 mm
Other Features	Normal Axial Internal Clearance
Keyword String	Angular Contact
cage material:	Brass
Limiting speed	3800 r/min
overall width:	49 mm
contact angle:	40 °
fillet radius:	2.5 mm
Reference speed	3800 r/min
finish/coating:	Uncoated
Rolling Element	Ball Bearing
Precision Class	ABEC 3 ISO P6
Long Description	105MM Bore; 225MM Outside Diameter; 49MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Balls; ABEC 3 ISO P6; No Filling Slot; No Snap Ring
Manufacturer URL	http://www.skf.com
Outside Diameter	8.858 Inch 225 Millimeter
precision rating:	ABEC 3 (ISO Class 6)
outer ring width:	49 mm
Manufacturer Name	SKF
outside diameter:	225 mm
Weight / Kilogram	9.12
r _b max.	1 mm
Bore Diameter (mm)	225
D _a max.	211 mm
D _b max.	218 mm
r _a max.	2.5 mm

d _a min.	119 mm
Internal Clearance	CB
Number of Bearings	1 (Single)
internal clearance:	C0
Outer Diameter (mm)	105
Calculation factor A	0.669
d _a - min.	119 mm
r _a - max.	2.5 mm
D _b - max.	218 mm
Mounting Arrangement	Universal
Minimum Buy Quantity	N/A
r _{1,2} min.	3 mm
D _a - max.	211 mm
r _{3,4} min.	1.1 mm
Calculation factor X	0.57
Calculation factor e	1.14
r _b - max.	1 mm
D ₁ ?	181.35 mm
d ₂ ?	127.87 mm
d ₁ ?	151.65 mm
row type & fill slot:	Single-Row Non-Fill Slot
Calculation factor - X	0.35
Calculation factor - e	1.14
r _{1,2} - min.	3 mm
Harmonized Tariff Code	8482.10.50.28
r _{3,4} - min.	1.1 mm
Number of Rows of Balls	Single Row
Manufacturer Item Number	7321 BECBM
Basic dynamic load rating C	216 kN
radial static load capacity:	208 kN

Basic dynamic load rating - C	216 kN
radial dynamic load capacity:	216 kN
Maximum Capacity / Filling Slot	No
Calculation factor k_r	0.1
Calculation factor Y_1	0.55
Calculation factor Y_2	0.93
Calculation factor Y_0	0.52
Fatigue load limit P_u	6.95 kN
Calculation factor - Y_2	0.57
Calculation factor - k_r	0.1
Calculation factor - Y_0	0.26
Calculation factor - Y_1	
Fatigue load limit - P_u	7 kN
Calculation factor - k_a	1.6
Basic static load rating C_0	208 kN
Basic static load rating - C_0	208 kN