




Bearing No. NUP 307 ECML

F	46.2 mm
d	35 mm
D	80 mm
B	21 mm
Size (mm)	80x35x21
Width (mm)	21
Mass bearing	0.58 kg
d ₁	51 mm
D ₁	66.3 mm
Limiting speed	11000 r/min
Bearing number	NUP 307 ECML
Reference speed	9500 r/min
Limiting value e	0.2
d _a min.	44 mm
D _a max.	72.2 mm
r _a max.	1.5 mm
Bore Diameter (mm)	80
d _b min.	53 mm
Outer Diameter (mm)	35
Axial load factor Y	0.6
r _a - max.	1.5 mm
D _a - max.	72.2 mm
d _b - min.	53 mm
d _a - min.	44 mm
r _{1,2} min.	1.5 mm
r _{3,4} min.	1.1 mm
d ₁ ?	51 mm
D ₁ ?	66.3 mm
r _{1,2} - min.	1.5 mm
r _{3,4} - min.	1.1 mm

Basic dynamic load rating C	75 kN
Basic dynamic load rating - C	75 kN
Fatigue load limit P_u	8.15 kN
Calculation factor k_r	0.23
Calculation factor - k_r	0.23
Fatigue load limit - P_u	8.2 kN
Basic static load rating C_0	63 kN
Basic static load rating - C_0	63 kN