




Bearing No. 6210

D	90 mm
d	50 mm
B	20 mm
C	20 mm
f0	14.4
Cu	1.55
Cr	43.9
C0r	23.3
Bore	1.969 Inch 50 Millimeter
Noun	Bearing
UNSPSC	31171504
Weight	0,463 Kg
r(min)	1.1
r min.	1,1 mm
da min.	56,5 mm
ra(max)	1
Da max.	83,5 mm
Da(max)	83.5
da(min)	56.5
ra max.	1 mm
Category	Single Row Ball Bearing
Oil lub.	8500
Inventory	0.0
Enclosure	Open
Size (mm)	50x90x20
Snap Ring	No
Width (mm)	20
Grease lub.	7100
Bearing No.	6210

Weight / LBS	1.104
Product Group	B00308
Cage Material	Steel
Inch - Metric	Metric
Keyword String	Ball
Bearing number	6210
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outer Race Width	0.787 Inch 20 Millimeter
Long Description	50MM Bore; 90MM Outside Diameter; 20MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Outside Diameter	3.543 Inch 90 Millimeter
(Refer.)Mass(kg)	0.463
Manufacturer URL	http://www.koyousa.com
Weight / Kilogram	0.501
Manufacturer Name	KOYO
Internal Clearance	C0-Medium
Bore Diameter (mm)	50
Outer Diameter (mm)	90
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	8500 r/min
Manufacturer Item Number	6210
Internal Special Features	No
(Grease) Lubrication Speed	7100 r/min

Basic static load rating (C0)	23,3 kN
Basic dynamic load rating (C)	35,1 kN
Maximum Capacity / Filling Slot	No