




Bearing No. 7208DT

D	80 mm
a	8.3 mm
C	18 mm
B	18 mm
d	40 mm
r1	0.6 mm
2B	36 mm
Width	18 mm
r min.	1.1 mm
Weight	0.380 Kg
ra max.	0.6 mm
r1 min.	0.6 mm
da min.	45 mm
Da max.	75 mm
ra (max)	1 mm
da1 (min)	47 mm
Bore Size	40 mm
Enclosure	Open
Bore Type	Cylindrical Bore
ra1 (max)	0.6 mm
Size (mm)	40x80x18
da2 (min)	45 mm
Da2 (max)	75 mm
Da1 (max)	73 mm
Width (mm)	18
Configuration	Duplex
Bearing number	7208DT
Angle (?)	30 °
Outside Diameter	80 mm
Static Load Rating	50,500 N

Bore Diameter (mm)	40
Dynamic Load Rating	57,500 N
Outer Diameter (mm)	80
Limiting Speed - Oil	8,000 rpm
Fillet Radius/Chamfer	1.1 mm
Limiting Speed - Grease	6,000 rpm
(Grease) Lubrication Speed	6000 r/min
Basic dynamic load rating (C)	57,5 kN
Basic static load rating (C0)	50,5 kN