



Bearing No. 43131/43312

e	0.67
d	33,338 mm
D	79,375 mm
T	25,4 mm
B	24,074 mm
C	17,462 mm
a	23,7 mm
Da	67 mm
B_	24.074
Db	74 mm
da	51 mm
Y0	0.49
db	42 mm
C0	69.5
D_	79.375
Z_	13
C_	17.462
Y1	0.9
DE_	64.978
SLR	15.8
D_a	67
DI_	44.235
DA1	12.305
DA2	10.129
CUP	0.22
DA_	11.234
D_b	74
RAr	88.228
SDM_	54.948
KBRG	3161

yobi	43131/43312
CONE	0.348
ALP21	48
ALP22	0
ALP23	0
BETA_	4
BET21	8
BET23	0
BET22	0
r min.	3,5 mm
LangID	1
Weight	0,568 Kg
ALPHA_	24
r1 min.	1,5 mm
ra max.	3,5 mm
Oil rpm	6700
outer r	1.5
hidYobi	43131/43312
GRS rpm	5000
inner r	3.5
hidTable	ecat_NSTPRI
inner ra	3.5
outer rb	1.5
ra1 max.	1,5 mm
Size (mm)	33.338x79.375x25.4
SHOG_yobi	43131R/43312R
Prod_Type3	TRBSR_ID_A
Width (mm)	25,4
Bearing number	43131/43312
Bore Diameter (mm)	33,338
Outer Diameter (mm)	79,375
Calculation factor (e)	0,67

(Oil) Lubrication Speed	6700 r/min
Calculation factor (Y0)	0,49
(Grease) Lubrication Speed	5000 r/min
Basic static load rating (C0)	69,5 kN
Basic dynamic load rating (C)	67,5 kN