



Bearing No. 57008R

C	12 mm
e	0.52
d	20 mm
D	47 mm
T	15,25 mm
B	14 mm
a	12,9 mm
Y0	0.64
Y1	1.16
Cu	3.75
Cr	34.2
C0r	25.5
a(mm)	12.9
r min.	1 mm
da max	26 mm
Da min	37 mm
r(min)	1
Weight	0,125 Kg
r1(min)	1
db(max)	26
da(min)	25.5
Sb(min)	3
Da(max)	41.5
Sa(min)	2
Da(min)	37
ra(max)	1
rb(max)	1
Db(min)	44
rb max.	1 mm
ra max.	1 mm

Db min.	44 mm
Da max.	41,5 mm
da min.	25,5 mm
r2 min.	1 mm
Oil lub.	12000
Size (mm)	20x47x15.25
Width (mm)	15,25
Bearing No.	57008R
Grease lub.	9000
Bearing number	57008R
(Refer.)Mass(kg)	0.125
Bore Diameter (mm)	20
Outer Diameter (mm)	47
Calculation factor (e)	0,52
Calculation factor (Y0)	0,64
(Oil) Lubrication Speed	12000 r/min
(Grease) Lubrication Speed	9000 r/min
Basic static load rating (C0)	25,5 kN
Basic dynamic load rating (C)	25,8 kN