



Bearing No. 567A/563

|           |                   |
|-----------|-------------------|
| C         | 28,575 mm         |
| a         | 28,6 mm           |
| e         | 0.36              |
| d         | 71,438 mm         |
| D         | 127 mm            |
| T         | 36,512 mm         |
| B         | 36,17 mm          |
| db        | 80.0              |
| da        | 86.0              |
| Cr        | 196               |
| Da        | 112 mm            |
| Db        | 120 mm            |
| Cu        | 35.3              |
| Y1        | 1.65              |
| Y0        | 0.91              |
| C0r       | 226               |
| a(mm)     | 28.6              |
| Weight    | 1,838 Kg          |
| r(min)    | 3.6               |
| db min    | 80 mm             |
| r min.    | 3,6 mm            |
| ra max.   | 3,6 mm            |
| r1(min)   | 3.2               |
| rb(max)   | 3.2               |
| ra(max)   | 3.6               |
| da min.   | 86 mm             |
| r2 min.   | 3,2 mm            |
| rb max.   | 3,2 mm            |
| Oil lub.  | 4000              |
| Size (mm) | 71.438x127x36.512 |

|                               |            |
|-------------------------------|------------|
| Width (mm)                    | 36,512     |
| Bearing No.                   | 567A/563   |
| Grease lub.                   | 3000       |
| Bearing number                | 567A/563   |
| (Refer.)Mass(kg)              | 1.84       |
| Bore Diameter (mm)            | 71,438     |
| Outer Diameter (mm)           | 127        |
| Calculation factor (e)        | 0,36       |
| Calculation factor (Y0)       | 0,91       |
| (Oil) Lubrication Speed       | 4000 r/min |
| (Grease) Lubrication Speed    | 3000 r/min |
| Basic dynamic load rating (C) | 156 kN     |
| Basic static load rating (C0) | 226 kN     |