



Bearing No. 6212DDU

r	1.5
d	60 mm
D	110 mm
B	22 mm
C	22 mm
D_	110
C0	36
Z_	10
ra	1.5
fo	14.3
B_	22
DI_	70.625
SRI	8.22
SRE	8.22
DE_	102.375
DA_	15.875
D_a	102
KBRG	6161
SBRG	2
SRIN	-0.03
bomp	0
SREX	0.03
yobi	6212DDU
SRIX	0.03
Bore	2.362 Inch 60 Millimeter
SDM_	86.5
SREN	-0.03
mass	0.783
Noun	Bearing

LangID	1
UNSPSC	31171504
da min	68
ALPHA_	0
r min.	1,5 mm
Weight	0,783 Kg
C_conv	52500
da max	74,5 mm
Da max.	102 mm
ra max.	1,5 mm
GRS rpm	3800
da min.	68 mm
hidYobi	6212DDU
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Size (mm)	60x110x22
Enclosure	2 Seals
Snap Ring	No
Inventory	0.0
Width (mm)	22
Prod_Type3	DGBB_SR_DD
Weight / LBS	1.7265
Inch - Metric	Metric
Product Group	B00308
Cage Material	Steel
Bearing number	6212DDU
Keyword String	Ball
Other Features	Deep Groove Rubber Seal
Enclosure Type	Contact Seal
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Outer Race Width	0.866 Inch 22

	Millimeter
Outside Diameter	4.331 Inch 110 Millimeter
Long Description	60MM Bore; 110MM Outside Diameter; 22MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Manufacturer URL	http://www.nskamericas.com
Inner Race Width	0 Inch 0 Millimeter
Manufacturer Name	NSK
Weight / Kilogram	0.791
Internal Clearance	C0-Medium
Bore Diameter (mm)	60
Outer Diameter (mm)	110
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6212DDU
Internal Special Features	No
(Grease) Lubrication Speed	3 800 r/min
Basic static load rating (C0)	36 kN
Basic dynamic load rating (C)	52,5 kN
Maximum Capacity / Filling Slot	No