



Bearing No. 6212NR

f	2,41 mm
d	60 mm
D	110 mm
B	22 mm
C	22 mm
a	3,28 mm
b	2,85 mm
Cr	65.6
f0	14.4
Cu	2.40
D2	116,6 mm
D1	106,81 mm
C0r	36.2
Bore	2.362 Inch 60 Millimeter
Noun	Bearing
r min.	1,5 mm
r(min)	1.5
UNSPSC	31171504
Weight	0,783 Kg
r1(min)	0.5
da(min)	68
D2(min)	116.6
Da(max)	102
rb(max)	0.5
ra(max)	1.5
Dx(min)	118
r0 max.	0,6 mm
r1 min.	0,5 mm
da min.	68 mm

Cy(max)	5.43
Da max.	102 mm
Category	Single Row Ball Bearing
Oil lub.	6900
Snap Ring	Yes
Size (mm)	60x110x22
Inventory	0.0
Enclosure	Open
Width (mm)	22
Grease lub.	5700
f(}0.05)	2.41
Bearing No.	6212NR
Weight / LBS	1.72622
Cage Material	Steel
Inch - Metric	Metric
Product Group	B00308
Bearing number	6212NR
Other Features	Deep Groove With Snap Ring
Keyword String	Ball
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Manufacturer URL	http://www.koyousa.com
Outer Race Width	0.866 Inch 22 Millimeter
(Refer.)Mass(kg)	0.783
Long Description	60MM Bore; 110MM Outside Diameter; 22MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; Yes Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage

Inner Race Width	0 Inch 0 Millimeter
Outside Diameter	4.331 Inch 110 Millimeter
Weight / Kilogram	0.865
Manufacturer Name	KOYO
Internal Clearance	C0-Medium
Bore Diameter (mm)	60
Outer Diameter (mm)	110
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
(Oil) Lubrication Speed	6900 r/min
Internal Special Features	No
(Grease) Lubrication Speed	5700 r/min
Basic static load rating (C0)	36,2 kN
Basic dynamic load rating (C)	52,4 kN
Maximum Capacity / Filling Slot	No