




Bearing No. 7211B

D	100 mm
d	55 mm
B	21 mm
C	21 mm
a	43.6 mm
Cu	2.15
Cr	57.7
f0	-
C0r	36.2
Noun	Bearing
Bore	2.165 Inch 55 Millimeter
a(mm)	43.6
Width	0.827 Inch 21 Millimeter
Weight	0.635 Kg
r min.	1.5 mm
UNSPSC	31171531
r(min)	1.5
da(min)	63.5
r1 min.	1 mm
Da max.	91.5 mm
r1(min)	1
Da(max)	91.5
ra max.	1.5 mm
ra(max)	1.5
da min.	63.5 mm
Category	Angular Contact Ball Bearing
Oil lub.	6000
Inventory	0.0

Enclosure	Open
Size (mm)	55x100x21
Snap Ring	No
Width (mm)	21
Bearing No.	7211B
Grease lub.	4500
Flush Ground	No
Contact Angle	40 Degree
Inch - Metric	Metric
Cage Material	Steel
Product Group	B00308
Keyword String	Angular Contact
Bearing number	7211B
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Angle (?)	40 °
(Refer.)Mass(kg)	0.635
Outside Diameter	3.937 Inch 100 Millimeter
Manufacturer URL	http://www.koyousa.com
Long Description	55MM Bore; 100MM Outside Diameter; 21MM Width; Open; No Flush Ground; Ball Bearing; Single Row of Balls; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; C0-Medium; Steel Cage; 40 Degree; 1 (Single)
Weight / Kilogram	0
Manufacturer Name	KOYO
Number of Bearings	1 (Single)
Internal Clearance	C0-Medium
Bore Diameter (mm)	55



Outer Diameter (mm)	100
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.28
Number of Rows of Balls	Single Row
(Grease) Lubrication Speed	5700 r/min
Maximum Capacity / Filling Slot	No