



Bearing No. 6212ZZ

r	1.5
d	60 mm
D	110 mm
B	22 mm
C	22 mm
Z_	10
B_	22
D_	110
fo	14.3
ra	1.5
C0	36
DI_	70.625
DE_	102.375
DA_	15.875
D_a	102
SRI	8.22
SRE	8.22
SRIX	0.03
SRIN	-0.03
Noun	Bearing
bomp	0
SREN	-0.03
SREX	0.03
Bore	2.362 Inch 60 Millimeter
mass	0.783
KBRG	6141
SBRG	2
yobi	6212ZZ
SDM_	86.5

Weight	0,783 Kg
LangID	1
r min.	1,5 mm
ALPHA_	0
UNSPSC	31171504
da min	68
C_conv	52500
da max	74,5 mm
da min.	68 mm
GRS rpm	5600
hidYobi	6212ZZ
ra max.	1,5 mm
Da max.	102 mm
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Enclosure	2 Metal Shields
Size (mm)	60x110x22
Inventory	0.0
Snap Ring	No
Width (mm)	22
Prod_Type3	DGBB_SR_ZZ
Weight / LBS	0.775
Product Group	B00308
Inch - Metric	Metric
Cage Material	Steel
Bearing number	6212ZZ
Keyword String	Ball
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
Manufacturer URL	http://www.nskamericas.com
Outside Diameter	4.331 Inch 110 Millimeter

Outer Race Width	0.866 Inch 22 Millimeter
Long Description	60MM Bore; 110MM Outside Diameter; 22MM Outer Race Diameter; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Manufacturer Name	NSK
Weight / Kilogram	0.78
Internal Clearance	C0-Medium
Bore Diameter (mm)	60
Outer Diameter (mm)	110
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6212ZZ
Internal Special Features	No
(Grease) Lubrication Speed	5 600 r/min
Basic static load rating (C0)	36 kN
Basic dynamic load rating (C)	52,5 kN
Maximum Capacity / Filling Slot	No