



Bearing No. 56425/56650

e	0.5
d	107,95 mm
D	165,1 mm
T	36,512 mm
B	36,512 mm
C	26,988 mm
a	38,6 mm
Da	149 mm
B_	36.512
Db	159 mm
da	123 mm
Y0	0.66
db	117 mm
C0	320
D_	165.1
Z_	27
C_	26.988
Y1	1.2
DE_	148.273
SLR	25.65
D_a	149
DI_	123.528
DA1	13.759
DA2	12.347
CUP	0.861
DA_	13.059
D_b	159
RAr	248.996
SDM_	136.155
KBRG	3161

yobi	56425/56650
CONE	1.8
ALP21	36
ALP22	38
ALP23	0
BETA_	1
BET21	3
BET23	0
BET22	10
r min.	3,5 mm
LangID	1
Weight	2,661 Kg
ALPHA_	18.333
r1 min.	3,3 mm
ra max.	3,5 mm
Oil rpm	2600
outer r	3.3
hidYobi	56425/56650
GRS rpm	2000
inner r	3.5
hidTable	ecat_NSTPRI
inner ra	3.5
outer rb	3.3
ra1 max.	3,3 mm
Size (mm)	107.95x165.1x36.512
SHOG_yobi	56425/56650
Prod_Type3	TRBSR_ID_A
Width (mm)	36,512
Bearing number	56425/56650
Bore Diameter (mm)	107,95
Outer Diameter (mm)	165,1
Calculation factor (e)	0,5

(Oil) Lubrication Speed	2600 r/min
Calculation factor (Y0)	0,66
(Grease) Lubrication Speed	2000 r/min
Basic static load rating (C0)	320 kN
Basic dynamic load rating (C)	195 kN