



Bearing No. 7212C

a	-1.2 mm
d	60 mm
D	110 mm
B	22 mm
C	22 mm
r1	1 mm
a -	1,2 mm
Width	22 mm
Weight	0,82 Kg
r min.	1,5 mm
ra max.	1.5 mm
Da max.	101 mm
da min.	69 mm
r1 min.	1 mm
ra (max)	1.5 mm
Da1 (max)	101 mm
Da2 (max)	104.6 mm
da2 (min)	69 mm
da1 (min)	69 mm
Size (mm)	60x110x22
Enclosure	Open
Bore Type	Cylindrical Bore
Bore Size	60 mm
ra1 (max)	1 mm
Width (mm)	22
Configuration	Single Row
Bearing number	7212C
Angle (?)	15 °
Outside Diameter	110 mm
Static Load Rating	49,500 N

Bore Diameter (mm)	60
Dynamic Load Rating	64,500 N
Outer Diameter (mm)	110
Limiting Speed - Oil	13,000 rpm
Fillet Radius/Chamfer	1.5 mm
Limiting Speed - Grease	9,400 rpm
(Grease) Lubrication Speed	13700 r/min
Basic static load rating (C0)	49,5 kN
Basic dynamic load rating (C)	64,5 kN