




Bearing No. 7212CDB

C	22 mm
d	60 mm
B	22 mm
D	110 mm
r1	1 mm
2B	44 mm
a -	1.2 mm
Width	22 mm
r min.	1.5 mm
Weight	0.820 Kg
ra max.	1 mm
r1 min.	1 mm
da min.	69 mm
Da max.	104.6 mm
ra (max)	1.5 mm
da1 (min)	69 mm
Bore Size	60 mm
Enclosure	Open
Bore Type	Cylindrical Bore
ra1 (max)	1 mm
Size (mm)	60x110x22
da2 (min)	69 mm
Da2 (max)	104.6 mm
Da1 (max)	101 mm
Width (mm)	22
Configuration	Duplex
Bearing number	7212CDB
Angle (?)	15 °
Outside Diameter	110 mm
Static Load Rating	98,500 N

Bore Diameter (mm)	60
Dynamic Load Rating	105,000 N
Outer Diameter (mm)	110
Limiting Speed - Oil	10,000 rpm
Fillet Radius/Chamfer	1.5 mm
Limiting Speed - Grease	7,500 rpm
(Grease) Lubrication Speed	7500 r/min
Basic dynamic load rating (C)	105 kN
Basic static load rating (C0)	98,5 kN