



Bearing No. 7212CGD2/GNP4

B	22 mm
C	22 mm
d	60 mm
D	110 mm
Noun	Bearing
Bore	2.362 Inch 60 Millimeter
Width	1.732 Inch 44 Millimeter
UNSPSC	31171531
series:	72C
Preload	Light
Category	Precision Ball Bearings
Inventory	0.0
Size (mm)	60x110x22
Enclosure	Open
Width (mm)	22
duplex type:	Universal Flush Ground
Flush Ground	Yes
Weight / LBS	3.351
Inch - Metric	Metric
Cage Material	Nylon
Raceway Style	1 Rib Outer Ring
Product Group	B04270
Contact Angle	15 Degree
closure type:	Open
bore diameter:	60 mm
cage material:	Nylon
overall width:	44 mm
contact angle:	15 °
Keyword String	Angular Contact Ball

fillet radius:	1.5 mm
Bearing number	7212CGD2/GNP4
Other Features	Single Row Angular Contact
Precision Class	ABEC 7 ISO P4
Rolling Element	Ball Bearing
Material - Ball	Steel
Angle (?)	15 °
finish/coating:	Uncoated
Manufacturer URL	http://www.ntnamerica.com
Outside Diameter	4.331 Inch 110 Millimeter
Long Description	60MM Bore; 110MM Outside Diameter; 44MM Width; Open Enclosure; ABEC 7 ISO P4 Precision; Steel Ball Material; 2 (1 Pair) Bearings; 15 Degree Contact Angle; Nylon Cage Material; 1 Rib Outer Ring Racew
bearing material:	High Carbon Chrome Steel
Manufacturer Name	NTN
inner ring width:	22 mm
precision rating:	ISO Class 4
Weight / Kilogram	1.52
outside diameter:	110 mm
outer ring width:	22 mm
Number of Bearings	2 (1 Pair)
Bore Diameter (mm)	60
maximum rpm (oil):	10000 rpm
Outer Diameter (mm)	110
internal clearance:	C0

Minimum Buy Quantity	N/A
Mounting Arrangement	Duplex-Universal
maximum rpm (grease):	7700 rpm
Harmonized Tariff Code	8482.10.50.28
Manufacturer Item Number	7212CGD2/GNP4
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
radial static load capacity:	99000 N
radial dynamic load capacity:	104000 N