



Bearing No. 6214DDU

r	1.5
d	70 mm
D	125 mm
B	24 mm
C	24 mm
D_	125
C0	44
Z_	10
ra	1.5
fo	14.5
B_	24
DI_	80.038
SRI	9.04
SRE	9.04
DE_	114.962
DA_	17.462
D_a	117
KBRG	6161
SBRG	2
SRIN	-0.03
bomp	0
SREX	0.03
yobi	6214DDU
SRIX	0.03
Bore	2.756 Inch 70 Millimeter
SDM_	97.5
SREN	-0.03
mass	1.09
Noun	Bearing

LangID	1
UNSPSC	31171504
da min	78
ALPHA_	0
r min.	1,5 mm
Weight	1,09 Kg
C_conv	62000
da max	84 mm
Da max.	117 mm
ra max.	1,5 mm
GRS rpm	3400
da min.	78 mm
hidYobi	6214DDU
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Size (mm)	70x125x24
Enclosure	2 Seals
Snap Ring	No
Inventory	0.0
Width (mm)	24
Prod_Type3	DGBB_SR_DD
Weight / LBS	2.4035
Inch - Metric	Metric
Product Group	B00308
Cage Material	Steel
Bearing number	6214DDU
Keyword String	Ball
Other Features	Deep Groove Rubber Seal
Enclosure Type	Contact Seal
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Inner Race Width	0 Inch 0 Millimeter

Outer Race Width	0.945 Inch 24 Millimeter
Long Description	70MM Bore; 125MM Outside Diameter; 24MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Manufacturer URL	http://www.nskamericas.com
Outside Diameter	4.921 Inch 125 Millimeter
Manufacturer Name	NSK
Weight / Kilogram	1.1
Internal Clearance	C0-Medium
Bore Diameter (mm)	70
Outer Diameter (mm)	125
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6214DDU
Internal Special Features	No
(Grease) Lubrication Speed	3 400 r/min
Basic static load rating (C0)	44 kN
Basic dynamic load rating (C)	62 kN
Maximum Capacity / Filling Slot	No