



Bearing No. 45291/45220

|                                 |                      |
|---------------------------------|----------------------|
| R                               | 6,3 mm               |
| d                               | 57,15 mm             |
| D                               | 104,775 mm           |
| T                               | 30,162 mm            |
| B                               | 30,958 mm            |
| C                               | 23,812 mm            |
| r                               | 3,3 mm               |
| Da                              | 99 mm                |
| Ab                              | 1,8 mm               |
| Aa                              | 2,1 mm               |
| Db                              | 93 mm                |
| da                              | 65 mm                |
| db                              | 76 mm                |
| a -                             | 8,1 mm               |
| Weight                          | 1,07 Kg              |
| Size (mm)                       | 57.15x104.775x30.162 |
| Width (mm)                      | 30,162               |
| Factor (K)                      | 1,76                 |
| Factor (G1)                     | 63,5                 |
| Factor (Cg)                     | 0,0256               |
| Factor (G2)                     | 16,9                 |
| Bearing number                  | 45291/45220          |
| Bore Diameter (mm)              | 57,15                |
| Outer Diameter (mm)             | 104,775              |
| Calculation factor (e)          | 0,33                 |
| Basic static load rating (C0)   | 189 kN               |
| Basic dynamic load rating (C1)  | 142 kN               |
| Basic dynamic load rating (C90) | 36,8                 |

|                                  |      |
|----------------------------------|------|
| Basic dynamic load rating (Ca90) | 20,9 |
|----------------------------------|------|