



Bearing No. 6215DDU

r	1.5
d	75 mm
D	130 mm
B	25 mm
C	25 mm
D_	130
C0	49.5
Z_	11
ra	1.5
fo	14.7
B_	25
DI_	86.038
SRI	9.04
SRE	9.04
DE_	120.962
DA_	17.462
D_a	122
KBRG	6161
SBRG	2
SRIN	-0.03
bomp	0
SREX	0.03
yobi	6215DDU
SRIX	0.03
Bore	2.953 Inch 75 Millimeter
SDM_	103.5
SREN	-0.03
mass	1.19
Noun	Bearing

LangID	1
UNSPSC	31171504
da min	83
r min.	1,5 mm
Weight	1,19 Kg
ALPHA_	0
C_conv	66000
da max	90 mm
GRS rpm	3200
Da max.	122 mm
ra max.	1,5 mm
da min.	83 mm
hidYobi	6215DDU
Category	Single Row Ball Bearing
hidTable	ecat_NSRDGB
Size (mm)	75x130x25
Enclosure	2 Seals
Snap Ring	No
Inventory	0.0
Width (mm)	25
Prod_Type3	DGBB_SR_DD
Weight / LBS	2.624
Inch - Metric	Metric
Product Group	B00308
Cage Material	Steel
Bearing number	6215DDU
Keyword String	Ball
Other Features	Deep Groove Rubber Seal
Enclosure Type	Contact Seal
Precision Class	ABEC 1 ISO P0
Rolling Element	Ball Bearing
Inner Race Width	0 Inch 0 Millimeter

Outside Diameter	5.118 Inch 130 Millimeter
Long Description	75MM Bore; 130MM Outside Diameter; 25MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Manufacturer URL	http://www.nskamericas.com
Outer Race Width	0.984 Inch 25 Millimeter
Manufacturer Name	NSK
Weight / Kilogram	1.218
Internal Clearance	C0-Medium
Bore Diameter (mm)	75
Outer Diameter (mm)	130
Minimum Buy Quantity	N/A
Harmonized Tariff Code	8482.10.50.68
Manufacturer Item Number	6215DDU
Internal Special Features	No
(Grease) Lubrication Speed	3 200 r/min
Basic static load rating (C0)	49,5 kN
Basic dynamic load rating (C)	66 kN
Maximum Capacity / Filling Slot	No