




Bearing No. 6215ZZ

C	25 mm
d	75 mm
B	25 mm
D	130 mm
rn	0,5 mm
Bore	2.953 Inch 75 Millimeter
Noun	Bearing
UNSPSC	31171504
r min.	1,5 mm
da max	90,5 mm
Weight	1,18 Kg
series:	62
da min.	83 mm
Da max.	122 mm
ra max.	1,5 mm
Category	Single Row Ball Bearing
Size (mm)	75x130x25
Snap Ring	No
Enclosure	2 Metal Shields
Inventory	0.0
bore type:	Round
Width (mm)	25
Weight / LBS	2.54
maximum rpm:	5600 RPM
Cage Material	Steel
Product Group	B00308
Inch - Metric	Metric
closure type:	Double Shielded
Keyword String	Ball

Other Features	Deep Groove Shell Alvania Prelubricated
fillet radius:	1.5 mm
Bearing number	6215ZZ
bore diameter:	75 mm
cage material:	Steel
overall width:	25 mm
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
finish/coating:	Uncoated
Outside Diameter	5.118 Inch 130 Millimeter
Outer Race Width	0.984 Inch 25 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Long Description	75MM Bore; 130MM Outside Diameter; 25MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Ste
Manufacturer URL	http://www.ntnamerica.com
Weight / Kilogram	0
outer ring width:	25 mm
Manufacturer Name	NTN
bearing material:	High Carbon Chrome Steel
inner ring width:	25 mm
outside diameter:	130 mm
precision rating:	ISO Class 0
Internal Clearance	C0-Medium

Bore Diameter (mm)	75
Outer Diameter (mm)	130
internal clearance:	CN
snap ring included:	Without Snap Ring
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	4800 rpm
static load capacity:	49500 N
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	66000 N
Internal Special Features	No
(Grease) Lubrication Speed	4 800 r/min
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Basic static load rating (C0)	49,5 kN
Basic dynamic load rating (C)	66 kN
Maximum Capacity / Filling Slot	No