



**Bearing No. 467/453X**

|                                 |                       |
|---------------------------------|-----------------------|
| R                               | 0,8 mm                |
| d                               | 47,625 mm             |
| D                               | 104,775 mm            |
| T                               | 30,162 mm             |
| B                               | 29,317 mm             |
| C                               | 24,605 mm             |
| r                               | 3,3 mm                |
| Da                              | 98 mm                 |
| Ab                              | 1,4 mm                |
| Aa                              | 2,2 mm                |
| Db                              | 92 mm                 |
| da                              | 56 mm                 |
| db                              | 57 mm                 |
| a -                             | 7,1 mm                |
| Weight                          | 1,23 Kg               |
| Size (mm)                       | 47.625x104.775x30.162 |
| Width (mm)                      | 30,162                |
| Factor (K)                      | 1,74                  |
| Factor (G1)                     | 58,6                  |
| Factor (Cg)                     | 0,0248                |
| Factor (G2)                     | 17,1                  |
| Bearing number                  | 467/453X              |
| Bore Diameter (mm)              | 47,625                |
| Outer Diameter (mm)             | 104,775               |
| Calculation factor (e)          | 0,34                  |
| Basic static load rating (C0)   | 166 kN                |
| Basic dynamic load rating (C1)  | 126 kN                |
| Basic dynamic load rating (C90) | 32,6                  |
|                                 |                       |

|                                  |      |
|----------------------------------|------|
| Basic dynamic load rating (Ca90) | 18,7 |
|----------------------------------|------|