




Bearing No. 6218LLB

D	160 mm
d	90 mm
B	30 mm
C	30 mm
Noun	Bearing
Bore	3.543 Inch 90 Millimeter
r min.	2 mm
da max	109 mm
UNSPSC	31171504
Weight	2,15 Kg
Da max.	151 mm
ra max.	2 mm
da min.	99 mm
series:	62
Category	Single Row Ball Bearing
Inventory	0.0
Enclosure	2 Seals
Snap Ring	No
Size (mm)	90x160x30
bore type:	Round
Width (mm)	30
Weight / LBS	4.9604
maximum rpm:	4700 RPM
closure type:	Double Sealed
Cage Material	Steel
Product Group	B00308
Inch - Metric	Metric
Keyword String	Ball
Other Features	Deep Groove Non-Friction Nitrile Rubber

	Seal Shell Alvania Prelubricated
Enclosure Type	Non-Contact Seal
Bearing number	6218LLB
bore diameter:	90 mm
overall width:	30 mm
cage material:	Steel
fillet radius:	2 mm
Rolling Element	Ball Bearing
Precision Class	ABEC 1 ISO P0
finish/coating:	Uncoated
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	1.181 Inch 30 Millimeter
Outside Diameter	6.299 Inch 160 Millimeter
Long Description	90MM Bore; 160MM Outside Diameter; 30MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage;
Manufacturer URL	http://www.ntnamerica.com
Weight / Kilogram	0
outer ring width:	30 mm
Manufacturer Name	NTN
bearing material:	High Carbon Chrome Steel
inner ring width:	30 mm
outside diameter:	160 mm
precision rating:	ISO Class 0

Internal Clearance	C0-Medium
Bore Diameter (mm)	90
Outer Diameter (mm)	160
internal clearance:	CN
snap ring included:	Without Snap Ring
Minimum Buy Quantity	N/A
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	4000 rpm
static load capacity:	71500 N
Harmonized Tariff Code	8482.10.50.68
dynamic load capacity:	96000 N
Internal Special Features	No
(Grease) Lubrication Speed	4 000 r/min
manufacturer product page:	Click here
operating temperature range:	-40 to 120 °C
Basic static load rating (C0)	71,5 kN
Basic dynamic load rating (C)	96 kN
Maximum Capacity / Filling Slot	No