



Bearing No. 46T30324JR/101

| | |
|-------------|----------------|
| e | 0.35 |
| d | 120 mm |
| D | 260 mm |
| T | 128 mm |
| C | 101 mm |
| Y0 | 1.91 |
| Y3 | 2.91 |
| Cu | 89.9 |
| Y2 | 1.96 |
| Cr | 1220 |
| C0r | 1430 |
| r(min) | 3 |
| Weight | 30,6 Kg |
| Da min | 239 mm |
| r min. | 3 mm |
| r1(min) | 1 |
| Sa(min) | 13.5 |
| ra(max) | 3 |
| da(min) | 138 |
| rb(max) | 1 |
| Da(min) | 254 |
| rb max. | 1 mm |
| ra max. | 3 mm |
| da min. | 138 mm |
| r1 min. | 1 mm |
| Oil lub. | 1600 |
| Size (mm) | 120x260x128 |
| Width (mm) | 128 |
| Bearing No. | 46T30324JR/101 |
| Grease lub. | 1200 |
| | |

| | |
|-------------------------------|----------------|
| Bearing number | 46T30324JR/101 |
| (Refer.)Mass(kg) | 30.6 |
| Bore Diameter (mm) | 120 |
| Outer Diameter (mm) | 260 |
| Calculation factor (e) | 0,35 |
| Calculation factor (Y0) | 1,91 |
| (Oil) Lubrication Speed | 1600 r/min |
| (Grease) Lubrication Speed | 1200 r/min |
| Basic static load rating (C0) | 1430 kN |
| Basic dynamic load rating (C) | 976 kN |