



Bearing No. 47685/47620

e	0.4
d	82,55 mm
D	133,35 mm
T	33,338 mm
B	33,338 mm
C	26,195 mm
a	29 mm
Da	119 mm
B_	33.338
Db	128 mm
da	90 mm
Y0	0.82
db	90 mm
C0	237
D_	133.35
Z_	23
C_	26.195
Y1	1.5
DE_	118.884
SLR	24
D_a	119
DI_	96.176
DA1	11.889
DA2	10.706
CUP	0.577
DA_	11.627
D_b	128
RAr	240.456
SDM_	107.583
KBRG	3161

yobi	47685/47620
CONE	1.18
ALP21	30
ALP22	8
ALP23	0
BETA_	1
BET21	2
BET23	0
BET22	50
r min.	0,8 mm
LangID	1
Weight	1,757 Kg
ALPHA_	15.083
r1 min.	3,3 mm
ra max.	0,8 mm
Oil rpm	3600
outer r	3.3
hidYobi	47685/47620
GRS rpm	2600
inner r	0.8
hidTable	ecat_NSTPRI
inner ra	0.8
outer rb	3.3
ra1 max.	3,3 mm
Size (mm)	82.55x133.35x33.338
SHOG_yobi	47685/47620
Prod_Type3	TRBSR_ID_A
Width (mm)	33,338
Bearing number	47685/47620
Bore Diameter (mm)	82,55
Outer Diameter (mm)	133,35
Calculation factor (e)	0,4

(Oil) Lubrication Speed	3600 r/min
Calculation factor (Y0)	0,82
(Grease) Lubrication Speed	2600 r/min
Basic static load rating (C0)	237 kN
Basic dynamic load rating (C)	154 kN