



Bearing No. 30TAB06DB

| | |
|-------------------------|------------------|
| D | 62 mm |
| d | 30 mm |
| B | 15 mm |
| C | 15 mm |
| r1 | 0.6 mm |
| 2B | 30 mm |
| Width | 15 mm |
| r min. | 1 mm |
| Weight | 0.21 Kg |
| r1 min. | 0.6 mm |
| Da2 (max) | 53.4 mm |
| Enclosure | Open |
| Da1 (max) | 46 mm |
| da2 (min) | 39.7 mm |
| da1 (min) | 46.2 mm |
| Bore Size | 30 mm |
| Bore Type | Cylindrical Bore |
| Size (mm) | 30x62x15 |
| Width (mm) | 15 |
| Configuration | Double Row |
| Bearing number | 30TAB06DB |
| Angle (?) | 60 ° |
| Outside Diameter | 62 mm |
| Static Load Rating | 46,400 N |
| Bore Diameter (mm) | 30 |
| Dynamic Load Rating | 29,900 N |
| Outer Diameter (mm) | 62 |
| Limiting Speed - Oil | 6,000 rpm |
| Fillet Radius/Chamfer | 1 mm |
| Limiting Speed - Grease | 4,650 rpm |
| | |

| | |
|--------------------------------------|---------|
| Basic static load rating (C0) | 46,4 kN |
| Basic dynamic load rating (C) | 29,9 kN |
| Starting Torque - Grease Lubrication | 20 N·cm |