



Bearing No. 482/472X

|           |                      |
|-----------|----------------------|
| C         | 24,605 mm            |
| a         | 26 mm                |
| e         | 0.38                 |
| d         | 69,85 mm             |
| D         | 123,825 mm           |
| T         | 30,162 mm            |
| B         | 29,007 mm            |
| db        | 77.0                 |
| da        | 83.0                 |
| Cr        | 148                  |
| Da        | 109 mm               |
| Db        | 114 mm               |
| Cu        | 25.0                 |
| Y1        | 1.56                 |
| Y0        | 0.86                 |
| C0r       | 161                  |
| a(mm)     | 26.0                 |
| Weight    | 1,416 Kg             |
| r(min)    | 3.6                  |
| db min    | 77 mm                |
| r min.    | 3,6 mm               |
| ra max.   | 3,6 mm               |
| r1(min)   | 3.2                  |
| rb(max)   | 3.2                  |
| ra(max)   | 3.6                  |
| da min.   | 83 mm                |
| r2 min.   | 3,2 mm               |
| rb max.   | 3,2 mm               |
| Oil lub.  | 4200                 |
| Size (mm) | 69.85x123.825x30.162 |
|           |                      |

|                               |            |
|-------------------------------|------------|
| Width (mm)                    | 30,162     |
| Bearing No.                   | 482/472X   |
| Grease lub.                   | 3200       |
| Bearing number                | 482/472X   |
| (Refer.)Mass(kg)              | 1.42       |
| Bore Diameter (mm)            | 69,85      |
| Outer Diameter (mm)           | 123,825    |
| Calculation factor (e)        | 0,38       |
| Calculation factor (Y0)       | 0,86       |
| (Oil) Lubrication Speed       | 4200 r/min |
| (Grease) Lubrication Speed    | 3200 r/min |
| Basic dynamic load rating (C) | 118 kN     |
| Basic static load rating (C0) | 161 kN     |