



Bearing No. NJ2317R

|            |           |
|------------|-----------|
| C          | 60 mm     |
| d          | 85 mm     |
| D          | 180 mm    |
| B          | 60 mm     |
| B2         | -         |
| Cu         | 67.7      |
| Ew         | -         |
| d1         | -         |
| B1         | -         |
| Cr         | 491       |
| Fw         | 108 mm    |
| C0r        | 485       |
| r min.     | 3 mm      |
| Weight     | 6.98 Kg   |
| r(min)     | 3         |
| da(min)    | -         |
| db(min)    | 98        |
| db(max)    | 106       |
| dc(min)    | -         |
| r1(min)    | 3         |
| dd(min)    | -         |
| Da(max)    | 167       |
| Db(max)    | -         |
| Db(min)    | -         |
| r1 min.    | 3 mm      |
| ra(max)    | 2.5       |
| rb(max)    | 2.5       |
| Oil lub.   | 4400      |
| Size (mm)  | 85x180x60 |
| Width (mm) | 60        |
|            |           |

|                               |            |
|-------------------------------|------------|
| Grease lub.                   | 2900       |
| Bearing No.                   | NJ2317R    |
| Bearing number                | NJ2317R    |
| (Refer.)Mass(kg)              | 7.17       |
| Bore Diameter (mm)            | 85         |
| Outer Diameter (mm)           | 180        |
| (Grease) Lubrication Speed    | 2900 r/min |
| Basic static load rating (C0) | 485 kN     |
| Basic dynamic load rating (C) | 394 kN     |