



Bearing No. 629-RSH

D	26 mm
d	9 mm
B	8 mm
C	8 mm
d1	– mm
D1	22,6 mm
D2	0,3 mm
d2	13 mm
Weight	0,02 Kg
Da max.	23,6 mm
da min.	12,5 mm
ra max.	0,3 mm
r2 min.	11,4 mm
r1 min.	11,4 mm
Size (mm)	9x26x8
Width (mm)	8
Mass bearing	0.02 kg
Limiting speed	19000 r/min
Bearing number	629-RSH
Reference speed	– r/min
d _a min.	11.4 mm
d _a max.	12.5 mm
r _a max.	0.3 mm
Bore Diameter (mm)	9
D _a max.	23.6 mm
Outer Diameter (mm)	26
r _{1,2} min.	0.3 mm
D ₂ ?	22.6 mm
d ₂ ?	12.55 mm
Calculation factor (f0)	12

Fatigue load limit (P _u)	0,083
Basic dynamic load rating C	4.75 kN
Basic static load rating (C ₀)	1,96 kN
Basic dynamic load rating (C)	4,75 kN
Fatigue load limit P _u	0.083 kN
Calculation factor k _r	0.025
Calculation factor f ₀	12
Basic static load rating C ₀	1.96 kN