



Bearing No. 24188-B-K30 + AH24188-H

| | |
|----------------|--|
| l | 310 mm |
| e | 0,38 |
| D | 720 mm |
| B | 280 mm |
| a | 22 mm |
| b | 30 mm |
| m | 451 kg / Weight |
| d | 440 mm |
| Size (mm) | 420x720x280 |
| Width (mm) | 280 |
| d_s | 12,5 mm |
| C_r | 6400000 N / Dynamic load rating (radial) |
| n_s | 23,5 mm |
| D_1 | 612,4 mm |
| Y_1 | 1,76 |
| Y_2 | 2,62 |
| Y_0 | 1,72 |
| n_G | 710 1/min / Limiting speed |
| n_B | 255 1/min / Reference speed |
| m_1 | 42,9 kg / Weight, withdrawal sleeve |
| C_{0r} | 13200000 N / Static load rating (radial) |
| Bearing number | 24188-B-K30 + AH24188-H |
| d_{1H} | 420 mm |
| d_{2G} | Tr460X5 |
| | |

| | |
|--|---|
| C_{ur} | 1020000 N / Fatigue limit load, radial |
| r_{min} | 6 mm |
| $r_{a\ max}$ | 5 mm |
| $d_{a\ min}$ | 466 mm |
| $D_{a\ max}$ | 694 mm |
| Bore Diameter (mm) | 420 |
| Outer Diameter (mm) | 720 |
| - AH24188-H / Designation, withdrawal sleeve | AH24188H / Designation, withdrawal sleeve |