



Bearing No. 2308SK

| | |
|--------------------|-----------|
| e | 0.43 |
| d | 40 mm |
| D | 90 mm |
| B | 33 mm |
| C | 33 mm |
| Y0 | 1.5 |
| Y2 | 2.3 |
| Y1 | 1.5 |
| Mass | 0.89 kg |
| ra max | 1.5 mm |
| Da max | 82 mm |
| Ce min | 5 mm |
| db min | 45 mm |
| da max | 52 mm |
| da min | 48 mm |
| rs min | 1.5 mm |
| Weight | 0,889 Kg |
| r min. | 1,5 mm |
| Da max. | 82 mm |
| da min. | 48 mm |
| ra max. | 1,5 mm |
| Size (mm) | 40x90x33 |
| Width (mm) | 33 |
| Nlim (oil) | 8,000 rpm |
| Nlim (grease) | 6,300 rpm |
| Bearing number | 2308SK |
| Precision class | P0 |
| Dynamic load, C | 45.5 kN |
| Static load, C0 | 13.5 kN |
| Bore Diameter (mm) | 40 |
| | |

| | |
|---------------------------------|-------------|
| Outer Diameter (mm) | 90 |
| Radial clearance class | CN |
| Calculation factor (e) | 0,43 |
| (Oil) Lubrication Speed | 8 000 r/min |
| Calculation factor (Y1) | 1,5 |
| Calculation factor (Y0) | 1,5 |
| (Grease) Lubrication Speed | 6 300 r/min |
| Associated sleeve reference | H2308X |
| Basic dynamic load rating (C) | 45,5 kN |
| Basic static load rating (C0) | 13,5 kN |
| Min operating temperature, Tmin | -20 °C |
| Max operating temperature, Tmax | 120 °C |